



SERVING THE SOUTHEAST SINCE 1995

FENCES, GATES, & ARBORS



PRIVACY FENCE

Additional Post Cap Styles Available

Custom Configurations Available Upon Request



ALBEMARLE

- Section Widths: 6' & 8'
- Available Heights: 4', 5' & 6'
- 1 3/4" x 5 1/2" Top Pocket Rail
- 1 3/4" x 5 1/2" Bottom Pocket Rail with Galvanized Insert
- 7/8" x 6" T&G Panels
- Standard with 5" x 5" Post & 5" Square Pyramid/Flat Caps

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



ALBEMARLE W/ LATTICE

- Section Widths: 6' & 8'
- Available Heights: 4', 5' & 6'
- 1 1/2" x 5 1/2" Top Rail w/ Bottom Slit for Lattice Panel
- 1 3/4" x 5 1/2" Middle Pocket Rail with Top Slit for Lattice Panel
- 1 3/4" x 5 1/2" Bottom Pocket Rail with Galvanized Insert
- 12" H Top Lattice Accent Panel
- 7/8" x 6" T&G Panels
- Standard with 5" x 5" Post & Pyramid (Flat) Caps

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



ALBEMARLE W/ STARBURST

- Section Widths: 6' & 8'
- Available Heights: 4', 5' & 6'
- 1 1/2" x 5 1/2" Top Ribbed Rail
- 1 3/4" x 5 1/2" Middle Pocket Rail
- 1 3/4" x 5 1/2" Bottom Pocket Rail with Galvanized Insert
- 1" x 1" Picket Starburst Accent Panel
- 7/8" x 6" T&G Panels
- Standard with 5" x 5" Post & Pyramid (Flat) Caps

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available

**Only Available in White and Tan*

AVAILABLE COLORS*:



WHITE



TAN



ADOBE

SEMI-PRIVACY FENCE

Additional Post Cap Styles Available

Custom Configurations Available Upon Request



SAVANNAH SEMI-PRIVATE:

- **Section Widths:** 6' & 8'
 - **Available Heights:** 4', 5' & 6'
 - 1½" x 5½" Ribbed Top Rail
 - 1½" x 5½" Bottom Pocket Rail with Galvanized Insert
 - 7⁄8" x 6" Ribbed Panel
 - Approx. Spacing Between Panels*: 1"
**Spacing will vary based on section width*
 - Standard with 5" x 5" Square Post & 5" Square Pyramid/Flat Caps
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available*



SAVANNAH W/ LATTICE SEMI-PRIVATE:

- **Section Widths:** 6' & 8'
 - **Available Heights:** 4', 5' & 6'
 - 1½" x 5½" Ribbed Top Rail
 - 1½" x 5½" Ribbed Middle Rail
 - 1½" x 5½" Ribbed Bottom Rail with Galvanized Insert
 - Top Lattice Panel Accent
 - 7⁄8" x 6" Ribbed Panel
 - Approx. Spacing Between Panels*: 1"
**Spacing will vary based on section width*
 - Standard with 5" x 5" Square Post & 5" Square Pyramid/Flat Caps
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available*



MCCALL SEMI-PRIVATE:

- **Section Widths:** 6' & 8'
 - **Available Heights:** 4', 5' & 6'
 - 2" x 3½" Top Rail
 - 2" x 3½" Bottom Rail with Galvanized Insert
 - 7⁄8" x 6" Ribbed Panel
 - Approx. Spacing Between Panels*: 1"
**Spacing will vary based on section width*
 - Standard with 4" x 4" Square Post & 4" Square Pyramid/Flat Caps
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available*



HATTERAS SEMI-PRIVATE:

- **Section Widths:** 6' (8' optional upon request)
 - **Available Heights:** 4', 5' & 6'
 - 3" x 3" Bottom & Top Rail*
**Galvanized Insert not standard, but available at an upcharge*
 - 7⁄8" x 6" Ribbed Panel
 - Approx. Spacing Between Panels*: 1"
**Spacing will vary based on section width*
 - Standard with 5" x 5" Square Post & 5" Square Pyramid/Flat Caps
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available*

AVAILABLE COLORS:



WHITE



TAN

PICKET FENCE

Additional Post Cap Styles Available

Custom Configurations Available Upon Request



ROUTED DARLINGTON PICKET:

- Section Widths: 6' & 8'
 - Available Heights: 4'
 - 2" x 3½" Routed Top Rail
 - 2" x 3½" Routed Bottom Rail*
**Aluminum Reinforcement in 8' Section*
 - 7⁄8" x 3" Picket
 - Approx. Picket Spacing*: 3"
**Spacing will vary based on section width*
 - Standard with 7⁄8" x 3" Dog Ear Picket Caps
**7⁄8" x 3" Spade Picket Caps Available Upon Request*
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



ROUTED TYLER PICKET:

- Section Widths: 6' & 8'
 - Available Heights: 4', 5', & 6'
 - 2" x 3½" Routed Top Rail
 - 2" x 3½" Routed Bottom Rail with Aluminum Reinforcement
 - 7⁄8" x 3" Picket
 - Approx. Picket Spacing*: 1¾"
**Spacing will vary based on section width*
 - Standard with 7⁄8" x 3" Dog Ear Picket Caps
**7⁄8" x 3" Spade Picket Caps Available Upon Request*
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



STRAIGHT/SCALLOP/STEP CHERAW PICKET:

- Section Widths: 6' & 8'
 - Available Heights: 4', 5', & 6'
 - 2" x 3½" Routed Top Rail
 - 1½" x 5½" Routed Bottom Rail with Aluminum Reinforcement
 - 1½" x 1½" Square Pickets
 - 1½" Sharp Picket Caps
 - Approx. Picket Spacing*: 1⅞"
**Spacing will vary based on section width*
 - Standard with 5" x 5" Square Post & 5" Square Pyramid/Flat Cap
**7⁄8" x 3" Spade Picket Caps Available Upon Request*
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



QUEEN ELIZABETH PICKET:

- Section Widths: 6'
 - Available Heights: 4'
 - 1¾" x 1¾" Routed Top & Bottom Rail
 - 1" x 1" Square Pickets
 - 1" Square Boyscout Picket Caps
 - Approx. Picket Spacing*: 3"
 - Standard with 4" x 4" Square Post & 4" Ball Cap
 - Three Options to Choose From: QE I, QE II, or QE III
- Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available

AVAILABLE COLORS:



WHITE



TAN



ADOBE



CLOSED TOP PICKET

Additional Post Cap Styles Available

Custom Configurations Available Upon Request



CONWAY CLOSED TOP PICKET:

- Section Widths: 6' & 8'
- Available Heights: 4' & 52" (Pool Code)
- 2" x 3½" Routed Top Rail
- 2" x 3½" Routed Bottom Rail with Aluminum Reinforcement
- 1½" x 1½" Square Pickets
- Standard with Routed Posts; Brackets shown

- Standard with 4" x 4" Square Post & 4" Flat Cap
- Approx. Picket Spacing*: 3½"
**Spacing will vary based on section width*

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available



MYRTLE BEACH PICKET:

- Section Widths: 6' & 8'
- Available Heights: 4', 5', & 6'
- 2" x 3½" Routed Top Rail
- 2" x 3½" Routed Middle Rail
- 2" x 3½" Routed Bottom Rail with Aluminum Reinforcement
- 1½" x 1½" Square Pickets

- Standard with 4" x 4" Square Post & 4" Flat Cap/Square Pyramid
- Approx. Picket Spacing*: 3½"
**Spacing will vary based on section width*

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available

RANCH RAIL FENCE



- All Rails Measure 1½" x 5½" & Available in Either 8' or 16' Lengths; 5" x 5" Square Vinyl Post & Your Choice of 5" Square Post Caps.
 - 2-Rail Fence—Standard 5' Post with 10½" Spacing Between Rails
 - 3-Rail Fence—Standard 7' Post with 10½" Spacing Between Rails
 - 4-Rail Fence—Standard 7' Post with 7" Spacing Between Rails

Matching single (3', 4', 5' width) & double drive (6', 8', 10' width) gates available

AVAILABLE COLORS:



WHITE



TAN



ADOBE

** Rail Fence Only Available in White and Tan*



HARDWARE DETAILS

ADJUSTABLE STAINLESS STEEL HINGE SET (H-1):

- Post Flange—3½" (H) x 3¼" (W) x 3¼" (D)
- Gate Flange—3½" (H) x 3¼" (W) x 1½" (D)
- Horizontally Adjustable

ADJUSTABLE STAINLESS STEEL NON-CLOSING HINGES: HEAVY DUTY (H-1-HD):

- Both Flanges—3½" (H) x 3⅜" (W) x 3⅜" (D)
- Heavy Duty ⅝" Threaded Rod
- Horizontally Adjustable

ADJUSTABLE SELF-CLOSING STAINLESS STEEL HINGE (H-6):

- Both Flanges—3½" (H) x 3¼" (W) x 1¼" (D)
- Enclosed Spring with Tension Adjustment
- Horizontally Adjustable

ADJUSTABLE WALL MOUNT STAINLESS STEEL HINGE SET (H-1-W):

- Gate Flange—3½" (H) x 3¼" (W) x 1½" (D)
- Wall Flange—3½" (H) x 6⅝" (W)
- Non-Self-Closing
- Horizontally Adjustable

STAINLESS STEEL POST LATCH (L-5):

- Strike Flange—1¾" (H) x 1¼" (W) x 3½" (D)
- Latch Flange—2½" (H) x 5½" (W) x 1½" (D)
- Allows Entry from Both Sides
- Mounts Around Corner of Post & Gate Frame
- Pad-Lockable on One Side Only
- Return Spring for Reversible Mounting

MAGNETIC POOL SAFETY LATCH (L-1):

- 19½" Latch Height Meets Pool Requirements
- 2" Horizontal and Vertical Adjustment
- Reversible Right- or Left-Hand Use
- Easy-Grip Release Knob
- Key Cylinder at 45° Angle for Easy Access

HEAVY-DUTY DROP RODS (CB-2 CANE BOLT):

- ⅝" Diameter
- Dual Guides
- Pad-Lockable
- Retention-Ears for Theft Prevention
- 24" & 48" Length Available

STAINLESS STEEL GATE ANTI-SAG KIT:

- Stainless Steel Attachment Screws Included
- 9' Cable Length
- Gate Wheel (GW)
- 2-Sided Stainless Steel Bracket & Spring
- Powder-Coated Finish



FENCE GATES & HARDWARE

Gates Available for All Fence Styles



ALBEMARLE PRIVACY SINGLE GATE

(H-1 HINGE SET & L-5 LATCH SHOWN)



ALBEMARLE PRIVACY SINGLE GATE WITH STARBURST

(H-1 HINGE SET & L-5 LATCH SHOWN)



SAVANNAH SEMI-PRIVACY DOUBLE DRIVE GATE WITH LATTICE

(H-1 HINGE SET & L-6 LATCH, CB-2 CANE BOLT SHOWN)



STEP CHERAW PICKET SINGLE GATE

(H-6 SELF CLOSING HINGE SET & L-1 POOL LATCH SHOWN)



ROUTED TYLER PICKET SINGLE GATE

(H-1 HINGE SET & L-5 LATCH SHOWN)

AVAILABLE COLORS:



BLACK



WHITE*

* Special Order Only

ARBORS



Custom Configurations Available Upon Request



GARDEN ARBOR:

- Three Designs to Choose From: Madrid, Barcelona, and Lyonne
- Custom Designed Garden Arbors are Available to Match Specific Fence Styles
- All Garden Arbors have an Installed Walkway Height of 7' and Width of 4'
- Beautiful and Virtually Maintenance-Free
- Great Addition to Enhance Yard

AVAILABLE COLORS:



WHITE



TAN



GREENVILLE ARBOR:

- Arbor Top Attached to 6½" x 6½" Posts
- Columns Available in Lengths of 8' or 10'
- Attached or Free-Standing Styles Available
- Arbor Top Comprised of 2" x 8" Support Beams & 2" x 6" Rails (Joists)
- Recommended Not to Set Posts Any Farther Than 12' Apart
- Includes: Rails, Posts, Decorative Skirts, Pergola Caps, Screws, Vinyl Clips, & Glue
- Mounting Hardware NOT Included; Recommended to use Aluminum Structural Mount with 6½" Adaptor Plate Kit for Concrete or Deck Installation; Can also use Treated Wood Post for In-Ground Installation

AVAILABLE COLORS:



WHITE



SUMMER BREEZE ARBOR:

- Arbor Top Attached to 5" x 5" Routed Square Posts
- Columns Available in Lengths of 8', 10', or 12'
- Attached or Free-Standing Styles Available
- Arbor Top Comprised of 2" x 6" Support Beams & 1½" x 5½" Rails or 1½" x 5½" Support Beams and Rails; 7/8" x 3" Top Slats with 3" Dog Ear Picket Caps
- Recommended Not to Set Posts Any Farther Than 12' Apart
- Includes: Rails, Posts, Skirts (Trim Rings), Pergola Caps, Screws, Screw Hole Plugs, & Glue
- Mounting Hardware NOT Included; Recommended to use 5" Gorill Post Mount or Aluminum Structural Mount with 5' Adaptor Plate Kit for Concrete or Deck Installation; Can also use Treated Wood Post for In-Ground Installation

AVAILABLE COLORS:



WHITE



608 QUEEN STREET • PO BOX 1137 • GRIFTON, NC 28530
OFFICE: 252.524.5000 • TOLL FREE: 888.262.3362 • carolinavp.com